

astraldiagnostics AFB Carbol Fuchsin Kinyoun

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 09 DEC 2022

SECTION 1: Identification

Identification

Product form : Mixture

Product name : AFB Carbol Fuchsin Kinyoun

Product code 6301-08

Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only.

Recommended use : Laboratory chemicals

Restrictions on use : Not for food, drug or household use

Supplier 1.3.

Astral Diagnostics Inc.

Logan Township NJ 08085 - United States

T+1 856 224 0900

800-441-0366 Technical Service; Monday-Friday: 8:00AM-5:00 PM, Eastern US Time

www.ethosbiosciences.com

Emergency telephone number

Emergency number : 800-424-9300 CHEMTREC (USA) -- 24 Hours/Day, 7 Days/Week

SECTION 2: Hazard(s) identification

Classification of the substance or mixture 2.1.

GHS US classification

Flammable liquids Category 3 H226 Flammable liquid and vapor

Acute toxicity (inhalation:dust.mist) Category 4 H332 Harmful if inhaled Skin corrosion/irritation Category 1B

H314 Causes severe skin burns and eye damage Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage

Germ cell mutagenicity Category 2 H341 Suspected of causing genetic defects

Carcinogenicity Category 1B H350 May cause cancer

Reproductive toxicity Category 2 H361 Suspected of damaging the unborn child. (oral, Inhalation)

Specific target organ toxicity (single exposure) Category 1 H370 Causes damage to organs (central nervous system, optic nerve, liver, kidneys) Specific target organ toxicity (repeated exposure) Category 2

H373 May cause damage to organs (liver, kidneys) through prolonged or repeated

exposure

Hazardous to the aquatic environment - Acute Hazard H402 Harmful to aquatic life

Category 3

Hazardous to the aquatic environment - Chronic Hazard

Category 3

Full text of H statements: see section 16

H412 Harmful to aquatic life with long lasting effects

GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)









Signal word (GHS US) : Danger

Hazard statements (GHS US) H226 - Flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H332 - Harmful if inhaled

H341 - Suspected of causing genetic defects

H350 - May cause cancer

H361 - Suspected of damaging the unborn child. (oral, Inhalation)

H370 - Causes damage to organs (central nervous system, optic nerve, liver, kidneys)

H373 - May cause damage to organs (liver, kidneys) through prolonged or repeated exposure

H402 - Harmful to aquatic life

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.

09 DEC 2022 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from sparks, open flames, heat, hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof ventilating, lighting, electrical equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe mist, vapors, spray.

P264 - Wash exposed skin thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

P310 - Immediately call a poison center or doctor/physician.

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2) to extinguish

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to comply with local, state and federal regulations.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification

: None under normal conditions

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Water	(CAS-No.) 7732-18-5	77	Not classified
Ethanol	(CAS-No.) 64-17-5	12	Flam. Liq. 2, H225
Phenol	(CAS-No.) 108-95-2	7	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Muta. 2, H341 STOT RE 2, H373 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Basic Fuchsin (Pararosaniline Hydrochloride)	(CAS-No.) 569-61-9	< 1	Carc. 1B, H350
Methanol	(CAS-No.) 67-56-1	3	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

09 DEC 2022 EN (English US) 2/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after skin contact Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately call a poison center or doctor/physician.

First-aid measures after eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

Symptoms/effects after inhalation

symptoms

Symptoms/effects

: Harmful if inhaled. Causes severe skin burns. Causes serious eye damage. Causes damage to organs (central nervous system, eyes (blindness)).

Causes severe skin burns and eye damage. Suspected of causing genetic defects. Suspected of damaging fertility or the unborn child. Causes damage to organs.

Danger of serious damage to health by prolonged exposure through inhalation. Harmful if

inhaled. May cause cancer by inhalation.

Symptoms/effects after skin contact Caustic burns/corrosion of the skin.

Symptoms/effects after eye contact Blindness. Corrosion of the eye tissue. Visual disturbances.

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

Immediate medical attention and special treatment, if necessary

Obtain medical assistance. Treat symptomatically.

SECTION 5: Fire-fighting measures

Suitable (and unsuitable) extinguishing media 5.1.

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

Hazardous decomposition products in case of

fire

: Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire : Eliminate all ignition sources if safe to do so. Keep container tightly closed and away from heat,

sparks and flame. Stop leak if safe to do so. This product is not to be used under conditions of

poor ventilation.

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Dike and contain spill. Remove ignition sources.

6.1.1. For non-emergency personnel

: Safety glasses. Protective clothing. Gloves. Face-shield. Protective equipment

Emergency procedures : Evacuate unnecessary personnel.

For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing mist, vapors, spray.

Ventilate area. **Emergency procedures**

Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

Methods for cleaning up Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

Reference to other sections

See section 8. Exposure controls and personal protection.

09 DEC 2022 EN (English US) 3/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Use only outdoors or in a well-ventilated area. Do not breathe mist, vapors, spray. Obtain special instructions before use. Use personal protective equipment as required. Do not

handle until all safety precautions have been read and understood.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after

handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight,

incompatible materials, Heat sources, Ignition sources. Keep container closed when not in use.

Incompatible products : Strong oxidizers.

Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

AFB Carbol Fuchsin Kinyoun		
No additional information available		
Phenol (108-95-2)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	19 mg/m³	
ACGIH OEL TWA [ppm]	5 ppm	
Basic Fuchsin (Pararosaniline Hydrochloride) (569	-61-9)	
No additional information available		
Water (7732-18-5)		
No additional information available		
Ethanol (64-17-5)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Ethanol	
ACGIH STEL (ppm)	1000 ppm	
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)	
Regulatory reference	ACGIH 2021	
Methanol (67-56-1)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Methanol	
ACGIH OEL TWA [ppm]	200 ppm	
ACGIH STEL (ppm)	250 ppm	
Remark (ACGIH)	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI	
Regulatory reference	ACGIH 2021	
USA - ACGIH - Biological Exposure Indices		
Local name	METHANOL	
Biological Exposure Indices (BEI)	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns	
Regulatory reference	ACGIH 2021	

09 DEC 2022 EN (English US) 4/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation. Material should be handled in a laboratory hood whenever possible.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Face shield. Gloves. Protective clothing. Safety glasses. Respiratory protection.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):











Other information:

Do not eat, drink, or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Dark red to red-violet

Odor : Phenol odor
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available

Flash point : 43 °C

: No data available Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) : Non flammable. : No data available Vapor pressure Relative vapor density at 20 °C No data available Relative density : No data available Soluble in water. Solubility Log Pow No data available : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties No data available

09 DEC 2022 EN (English US) 5/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information.

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates: Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts vigorously with strong oxidizers and acids.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Hydrogen chloride. Carbon monoxide. Carbon dioxide. Thermal decomposition generates: Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

AFB Carbol Fuchsin Kinyoun			
LD50 oral rat	4154 mg/kg		
LC50 Inhalation - Rat	2.45 mg/l		
ATE US (oral)	4154 mg/kg body weight		
ATE US (vapors)	2.45 mg/l/4h		
ATE US (dust, mist)	2.45 mg/l/4h		
Phenol (108-95-2)			
LD50 oral rat	650 mg/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))		
LD50 dermal rat	660 mg/kg (Equivalent or similar to OECD 402, 24 h, Rat, Female, Experimental value, Dermal, 7 day(s))		
ATE US (oral)	650 mg/kg body weight		
ATE US (dermal)	660 mg/kg body weight		
Basic Fuchsin (Pararosaniline Hydrochloride) (569-61-9)			
LD50 oral rat	5000 mg/kg		
ATE US (oral)	5000 mg/kg body weight		
Water (7732-18-5)			
LD50 oral rat	≥ 90000 mg/kg		
ATE US (oral)	90000 mg/kg body weight		
Ethanol (64-17-5)			
LD50 oral rat	10740 mg/kg (Rat; Experimental value,Rat; Experimental value)		
LD50 dermal rabbit	> 15800 mg/kg body weight (Rabbit, Experimental value, Dermal)		
LC50 Inhalation - Rat	125 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapors), 14 day(s))		
ATE US (oral)	10740 mg/kg body weight		

09 DEC 2022 EN (English US) 6/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)		
LD50 oral rat	1187 – 2769 mg/kg body weight (BASF test, Rat, Male / female, Experimental value, Aqueous solution, Oral, 7 day(s))	
LC50 Inhalation - Rat	128 mg/l air (BASF test, 4 h, Rat, Male / female, Experimental value, Inhalation (vapors))	
ATE US (oral)	100 mg/kg body weight	
ATE US (dermal)	300 mg/kg body weight	
ATE US (gases)	700 ppmV/4h	
ATE US (vapors)	3 mg/l/4h	
ATE US (dust, mist)	0.5 mg/l/4h	

Skin corrosion/irritation : Causes severe skin burns. Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Suspected of causing genetic defects.

Carcinogenicity May cause cancer.

Basic Fuchsin (Pararosaniline Hydrochloride) (569-61-9)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen

Reproductive toxicity : Suspected of damaging the unborn child. (oral, Inhalation).

STOT-single exposure : Causes damage to organs (central nervous system, optic nerve, liver, kidneys).

Methanol (67-56-1)	
STOT-single exposure	Causes damage to organs (liver, kidneys, central nervous system, optic nerve) (Dermal, oral).

STOT-repeated exposure : May cause damage to organs (liver, kidneys) through prolonged or repeated exposure.

Phenol (108-95-2)	
STOT-repeated exposure	May cause damage to organs (liver, kidneys) through prolonged or repeated exposure.

Aspiration hazard : Not classified Viscosity, kinematic No data available

Likely routes of exposure : Inhalation. Skin and eye contact.

Potential Adverse human health effects and

symptoms

Symptoms/effects

: Harmful if inhaled. Causes severe skin burns. Causes serious eye damage. Causes damage to

organs (central nervous system, eyes (blindness)).

: Causes severe skin burns and eye damage. Suspected of causing genetic defects. Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/effects after inhalation Danger of serious damage to health by prolonged exposure through inhalation. Harmful if

inhaled. May cause cancer by inhalation.

Symptoms/effects after skin contact : Caustic burns/corrosion of the skin.

Symptoms/effects after eye contact Blindness. Corrosion of the eye tissue. Visual disturbances.

Symptoms/effects after ingestion Swallowing a small quantity of this material will result in serious health hazard.

09 DEC 2022 EN (English US) 7/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.1. Toxicity	12.1	. Toxicit	y
----------------	------	-----------	---

Ecology - water : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Phenol (108-95-2)	
LC50 fish 1	8.9 mg/l (US EPA, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	3.1 mg/l (US EPA, 48 h, Ceriodaphnia dubia, Static system, Fresh water, Experimental value, Locomotor effect)
Ethanol (64-17-5)	
LC50 fish 1	15300 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

Methanol (67-56-1)	
LC50 fish 1	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi- static system. Fresh water, Experimental value, Locomotor effect)

12.2. Persistence and degradability

AFB Carbol Fuchsin Kinyoun		
Persistence and degradability	May cause long-term adverse effects in the environment.	
Phenol (108-95-2)		
Persistence and degradability	Biodegradable in the soil. Inhibits biodegradation processes in the soil. Readily biodegradable in water. Readily biodegradable in water in anaerobic conditions.	
Biochemical oxygen demand (BOD)	1.68 g O₂/g substance	
Chemical oxygen demand (COD)	2.28 g O₂/g substance	
ThOD	2.38 g O₂/g substance	
Basic Fuchsin (Pararosaniline Hydrochloride) (569-61-9)		
Persistence and degradability	Not established.	
Water (7732-18-5)		
Persistence and degradability	Not established.	
Ethanol (64-17-5)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	0.8 – 0.967 g O₂/g substance	
Chemical oxygen demand (COD)	1.7 g O₂/g substance	
ThOD	2.1 g O₂/g substance	
BOD (% of ThOD)	0.43	
Methanol (67-56-1)		
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O ₂ /g substance	
Chemical oxygen demand (COD)	1.42 g O₂/g substance	
ThOD	1.5 g O₂/g substance	

09 DEC 2022 EN (English US) 8/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

AFB Carbol Fuchsin Kinyoun		
Bioaccumulative potential	Not established.	
Phenol (108-95-2)		
BCF fish 1	17.5 (OECD 305: Bioconcentration: Flow-Through Fish Test, 3 h, Danio rerio, Flow-through system, Fresh water, Experimental value, Fresh weight)	
Log Pow	1.47 (Experimental value, Equivalent or similar to OECD 117, 30 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
Basic Fuchsin (Pararosaniline Hydrochloride) (569-61-9)		
Log Pow	-0.21	
Bioaccumulative potential	Not established.	
Water (7732-18-5)		
Bioaccumulative potential	Not established.	
Ethanol (64-17-5)		
BCF fish 1	1 (Other, 72 h, Cyprinus carpio, Static system, Fresh water, Read-across)	
Log Pow	-0.31 (Experimental value)	
Bioaccumulative potential	Not bioaccumulative.	
Methanol (67-56-1)		
BCF fish 1	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)	
Log Pow	-0.77 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

12.4. Mobility in soil

Phenol (108-95-2)	
Surface tension	71.3 mN/m (20 °C, 0.118 %)
Log Koc	1.15 – 1.86 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

Ethanol (64-17-5)	
Surface tension	22.31 mN/m (20 °C, 100 %)
Log Koc	0.2 (log Koc, Experimental value)
Ecology - soil	Highly mobile in soil.

Methanol (67-56-1)	
Surface tension	No data available in the literature
Log Koc	-0.89 – -0.21 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Other information : Avoid release to the environment.

9 DEC 2022 EN (English US) 9/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

Disposal methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to comply with local, state and federal regulations.

: Avoid release to the environment. Ecology - waste materials

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN2920 Corrosive liquids, flammable, n.o.s. (Phenol, ethanol), 8 (3), II

UN-No.(DOT) : UN2920

Proper Shipping Name (DOT) Corrosive liquids, flammable, n.o.s.

Phenol, ethanol

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger

Subsidiary risk (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 8 - Corrosive

3 - Flammable liquid



: 202



DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)

: 243 DOT Special Provisions (49 CFR 172.102)

: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal...... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

: C - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel. **DOT Vessel Stowage Location**

DOT Vessel Stowage Other : 25 - Protected from sources of heat,40 - Stow "clear of living quarters"

Emergency Response Guide (ERG) Number

Other information : No supplementary information available.

Transport by sea (IMDG)

UN-No. (IMDG) : 2920

Proper Shipping Name (IMDG) : CORROSIVE LIQUID, FLAMMABLE, N.O.S.

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : II - substances presenting medium danger

09 DEC 2022 EN (English US) 10/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Subsidiary risks (IMDG) : 3 - Flammable liquids

Limited quantities (IMDG) : 1 L

Air transport (IATA/ICAO)

UN-No. (IATA) : 2920

Proper Shipping Name (IATA) : Corrosive liquid, flammable, n.o.s.

Class (IATA) : 8 - Corrosives Packing group (IATA) : II - Medium Danger Subsidiary hazards (IATA) : 3 - Flammable liquids

SECTION 15: Regulatory information

15.1. US Federal regulations

AFB Carbol Fuchsin Kinyoun	
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation Health hazard - Acute toxicity (any route of exposure) Health hazard - Germ cell mutagenicity Health hazard - Carcinogenicity Health hazard - Reproductive toxicity Health hazard - Specific target organ toxicity (single or repeated exposure)

All components of this product are listed as Active, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Phenol	CAS-No. 108-95-2
Basic Fuchsin (Pararosaniline Hydrochloride)	CAS-No. 569-61-9
Water	CAS-No. 7732-18-5
Ethanol	CAS-No. 64-17-5
Methanol	CAS-No. 67-56-1

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Phenol	CAS-No. 108-95-2
Methanol	CAS-No. 67-56-1

Phenol (108-95-2)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Germ cell mutagenicity Health hazard - Acute toxicity (any route of exposure) Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation
Methanol (67-56-1)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb

Methanol (67-56-1)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Acute toxicity (any route of exposure) Health hazard - Specific target organ toxicity (single or repeated exposure)

15.2. International regulations

CANADA

Phenol (108-95-2)
Listed on the Canadian DSL (Domestic Substances List)

09 DEC 2022 EN (English US) 11/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List)

Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Basic Fuchsin (Pararosaniline Hydrochloride) (569-61-9)

Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program)

Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations



This product can expose you to Basic Fuchsin (Pararosaniline Hydrochloride), which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

: 09 DEC 2022 Revision date

Full text of H-statements:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard

: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can

NFPA reactivity

: 0 - Material that in themselves are normally stable, even

under fire conditions.

09 DEC 2022 EN (English US) 12/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Rati	nc
10	วเม

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

* - Chronic (long-term) health effects may result from repeated overexposure

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient

temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II & IIIA)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection :

H - Splash goggles, Gloves, Synthetic apron, Vapor respirator

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS US (GHS HazCom 2012)

Ethos Biosciences/Astral Diagnostics provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Ethos Biosciences/Astral Diagnostics . makes no representations or warranties, either expressed or implied of merchantability, fitness for particular purposes with respect to the information set forth herein or to which the information refers. Accordingly, Ethos Biosciences/Astral Diagnostics will not be responsible for damages resulting from the use of or reliance upon this information.

09 DEC 2022 EN (English US) 13/13