

SECTION 1: Identification

1.1. Identification

Product name : Tissue Marking Dye, Ultra Black
Product code : 7562-02, 7570

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only.
Recommended use : Laboratory chemicals
Restrictions on use : Not for food, drug or household use

1.3. Supplier

Astral Diagnostics Inc.
Logan Township NJ 08085 - United States
T +1 856 224 0900
800-441-0366 Technical Service; Monday-Friday: 8:00AM-5:00 PM, Eastern US Time
www.ethosbiosciences.com

1.4. Emergency telephone number

Emergency number : 800-424-9300 CHEMTREC (USA) -- 24 Hours/Day, 7 Days/Week

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable Liquid Category 3	Flammable liquid and vapor
Skin corrosion/irritation Category 1B Serious eye damage/eye irritation Category 2 Skin sensitization, Category 1	Causes severe skin burns and eye damage
Germ cell mutagenicity Category 2	Causes serious eye damage
Carcinogenicity Category 1A	May cause an allergic skin reaction
	Suspected of causing genetic defects
	May cause cancer

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor
H301 - Toxic if swallowed
H311 - Toxic in contact with skin
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H331 - Toxic if inhaled
H341 - Suspected of causing genetic defects
H350 - May cause cancer
H400 - Very toxic to aquatic life

Tissue Marking Dye, Ultra Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS-US) : P203 - Obtain, read and follow all safety instructions before use.
P210 - Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P264+P265 - Wash hands exposed skin thoroughly after handling. Do not touch eyes.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P301+P316 - IF SWALLOWED: Get emergency medical help immediately.
P302+P361+P354 - IF ON SKIN: Take off Immediately all contaminated clothing. Immediately rinse with water for several minutes.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P354+P338 - IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P318 - If exposed or concerned, get medical advice.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂) to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents/container to comply with local, state and federal regulations.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
ammonium hydroxide	(CAS No) 1336-21-6	< 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Aquatic Acute 1, H400
formaldehyde	(CAS No) 50-00-0	< 5	Flam. Liq. 3, H226 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapor), H331 Skin Corr. 1B, H314 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1A, H350
carbon black	(CAS No) 1333-86-4	11-20	Carc. 2, H351
water	(CAS No) 7732-18-5	Balance	Not classified

Full text of hazard classes and H-statements : see section 16

Tissue Marking Dye, Ultra Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapor.
Reactivity	: Flammable liquid and vapor.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe mist/vapors/spray.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

Tissue Marking Dye, Ultra Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : In the United States, refer to OSHA 1910.1048 for requirements for handling of formaldehyde solutions.
- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe mist/vapors/spray. Avoid contact with skin and eyes.
- Hygiene measures : Launder work clothing separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink, or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Incompatible materials : Oxidizing agent.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Formaldehyde (50-00-0)		
ACGIH	ACGIH Ceiling (mg/m ³)	0.37 mg/m ³
ACGIH	ACGIH Ceiling (ppm)	0.3 ppm
OSHA	OSHA PEL (TWA) (ppm)	0.75 ppm
OSHA	OSHA PEL (STEL) (ppm)	2 ppm
IDLH	US IDLH (ppm)	20 ppm
NIOSH	NIOSH REL (TWA) (ppm)	0.016 ppm
NIOSH	NIOSH REL (ceiling) (ppm)	0.1 ppm 15 min.

Ammonium Hydroxide (1336-21-6)		
ACGIH	ACGIH TWA (mg/m ³)	17 mg/m ³
ACGIH	ACGIH STEL (mg/m ³)	24 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	35 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
IDLH	US IDLH (ppm)	300 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	18 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	27 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	35 ppm

Water (7732-18-5)		
Not applicable		

Tissue Marking Dye, Ultra Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Black (1333-86-4)		
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (inhalable fraction)
ACGIH	ACGIH Remark	Confirmed Animal Carcinogen with Unknown Relevance to Humans
OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
IDLH	US IDLH (ppm)	1750 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	3.5 mg/m ³

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection: Protective gloves

Eye protection: Safety glasses

Skin and body protection: Wear suitable protective clothing

Respiratory protection: None needed with adequate ventilation. If the occupational exposure limit is exceeded, use an approved organic vapor respirator. Selection of respiratory protection depends on the contaminant type, form, and concentration. Select in accordance with OSHA 1910.134 or other applicable regulations and good industrial hygiene practice.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Slightly viscous liquid
Color : Blue
Odor : Pungent, characteristic
Odor threshold : No data available
pH : Not applicable
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : 42 °C / 107.6 °F
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : Not applicable.
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available
Relative density : No data available
Specific gravity / density : No data available
Solubility : No data available
Log Pow : No data available
Auto-ignition temperature Decomposition : No data available
temperature : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available

Tissue Marking Dye, Ultra Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Formaldehyde (50-00-0)	
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (vapors)	3 mg/l/4h
Ammonium Hydroxide (1336-21-6)	
LD50 oral rat	350 mg/kg
ATE US (oral)	350 mg/kg body weight
ATE US (vapors)	10.714 mg/l/4h
Carbon Black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg
Water (7732-18-5)	
LD50 oral rat	≥ 90000 mg/kg
ATE US (oral)	90000 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns and eye damage.
pH: n/a

Serious eye damage/irritation : Causes serious eye damage.
pH: n/a

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Suspected of causing genetic defects .

Carcinogenicity : May cause cancer .

Formaldehyde (50-00-0)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	2 - Known Human Carcinogens

Tissue Marking Dye, Ultra Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Causes damage to organs .
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralization, the product may represent a danger to aquatic organisms.

Formaldehyde (50-00-0)	
EC50 Daphnia 2	2 mg/l
Ammonium Hydroxide (1336-21-6)	
LC50 fish 1	0.16 - 1.1 mg/l (LC50; 96 h)
EC50 Daphnia 1	2.08 mg/l (LC50; 48 h)
Carbon Black (1333-86-4)	
EC50 Daphnia 1	5600 mg/l (Exposure time: 24 h - Species: Daphnia magna)

12.2. Persistence and degradability

Ammonium Hydroxide (1336-21-6)	
Persistence and degradability	Readily biodegradable in water. Ozonation in water. Biodegradable in the soil. No test data on mobility of the components available. Ozonation in the air.
Formaldehyde (50-00-0)	
Persistence and degradability	Readily biodegradable in water. No (test)data on mobility of the components available. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.64 g O ₂ /g substance
Chemical oxygen demand (COD)	1.06 g O ₂ /g substance
ThOD	1.068 g O ₂ /g substance
BOD (% of ThOD)	0.6
Water (7732-18-5)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Formaldehyde (50-00-0)	
Log Pow	-0.78 - 0.0
Bioaccumulative potential	Bioaccumulation: not applicable.

Tissue Marking Dye, Ultra Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to comply with local, state and federal regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

Formaldehyde (50-00-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ	100 lb
-----------	--------

SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb
---	--------

Ammonium Hydroxide (1336-21-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
--	---------

SARA Section 311/312 Hazard Classes	Health hazard - Acute toxicity (any route of exposure) Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation
-------------------------------------	--

All components of this product are listed and active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Ammonia solution	CAS-No. 1336-21-6	28%
------------------	-------------------	-----

15.2. International regulations

CANADA

Formaldehyde (50-00-0)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material
----------------------	--

Tissue Marking Dye, Ultra Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ammonia solution (1336-21-6)	
Listed on the Canadian DSL (Domestic Substances List)	
Carbon Black (1333-86-4)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

EU-Regulations

No additional information available

National regulations

Ammonia solution (1336-21-6)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
Formaldehyde (50-00-0)	
Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program) Listed on EPA Hazardous Air Pollutant (HAPS) Listed on the Canadian IDL (Ingredient Disclosure List)	
Carbon Black (1333-86-4)	
Listed on the Canadian IDL (Ingredient Disclosure List)	

15.3. US State regulations

Formaldehyde (50-00-0)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	40 µg/day
Carbon Black (1333-86-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

WARNING:

This product can expose you to Formaldehyde and Carbon Black, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Initial date : 11 DEC 2013
Revision date : 06 DEC 2022

Tissue Marking Dye, Ultra Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


Full text of H-statements:

H226	Flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H331	Toxic if inhaled
H341	Suspected of causing genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H400	Very toxic to aquatic life

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
SDS US (GHS HazCom 2012)

Ethos Biosciences/Astral Diagnostics provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Ethos Biosciences/Astral Diagnostics . makes no representations or warranties, either expressed or implied of merchantability, fitness for particular purposes with respect to the information set forth herein or to which the information refers. Accordingly, Ethos Biosciences/Astral Diagnostics will not be responsible for damages resulting from the use of or reliance upon this information.