

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
 Issue date: 7/17/2024 Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : Gram Stain, Decolorizer 75 25  
 Product code : all sizes of 6060C, 6254, 6504, & 6931

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only  
 For professional use only  
 Restrictions on use : Not for food, drug or household use

#### 1.3. Supplier

Astral Diagnostics  
 Ethos Biosciences, Inc.  
 2070 Center Square Road  
 Logan Township, New Jersey 08085  
 United States  
 T +1-856-224-0900; +1-800-441-0366 Technical Service; Monday-Friday: 8:00 AM-5:00 PM, Eastern US Time  
[www.ethosbiosciences.com](http://www.ethosbiosciences.com)

#### 1.4. Emergency telephone number

Emergency number : 800-424-9300 CHEMTREC (USA) -- 24 Hours/Day, 7 Days/Week

### SECTION 2: Hazard(s) identification




#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Carcinogenicity Category 1A	H350	May cause cancer
Specific target organ toxicity (single exposure) Category 1	H370	Causes damage to organs
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Full text of H statements : see section 16		

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :   

Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor  
 H319 - Causes serious eye irritation  
 H336 - May cause drowsiness or dizziness  
 H350 - May cause cancer  
 H370 - Causes damage to organs

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/Bond container and receiving equipment.  
P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P307+P311 - If exposed: Call a poison center/doctor.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P312 - Call a poison center or doctor if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	Conc.	GHS US classification
ethanol	CAS-No.: 64-17-5	71.25	Flam. Liq. 2, H225 Carc. 1A, H350
acetone	CAS-No.: 67-64-1	25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Methanol	CAS-No.: 67-56-1	3.75	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Full text of hazard classes and H-statements : see section 16

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

##### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Packaging materials : Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

acetone (67-64-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	250 ppm
ACGIH OEL STEL	500 ppm
ethanol (64-17-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethanol
ACGIH OEL STEL	1000 ppm

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethanol (64-17-5)	
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl alcohol (Ethanol)
OSHA PEL TWA	1900 mg/m³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Methanol (67-56-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Methanol
ACGIH OEL TWA	200 ppm
ACGIH OEL STEL	250 ppm
Remark (ACGIH)	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	Methanol
BEI	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Methyl alcohol
OSHA PEL TWA	260 mg/m³
	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

<b>Hand protection:</b>
Protective gloves
<b>Eye protection:</b>
Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

#### acetone

Boiling point	56 °C
Flash point	-17 °C (Closed cup)
Auto-ignition temperature	465 °C (T1)
Vapor pressure	240 hPa (20 °C)
Vapor pressure at 50°C	828 hPa

#### ethanol

Boiling point	78 °C (1013 hPa)
Flash point	13 °C (Closed cup, 1013.25 hPa)
Auto-ignition temperature	363 – 425 °C (1013.25 hPa, T2)
Vapor pressure	57 hPa (20 °C)
Vapor pressure at 50°C	300 hPa

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol	
Boiling point	65 °C (1013 hPa)
Flash point	10 °C (Closed cup, 1013 hPa, EU Method A.9: Flash-Point)
Auto-ignition temperature	455 °C (1013 hPa, DIN 51794: Self-ignition temperature, T1)
Vapor pressure	128 hPa (20 °C)
Vapor pressure at 50°C	552 hPa

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 15800 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	132 mg/l (3 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE US (oral)	5800 mg/kg body weight
ATE US (vapors)	132 mg/l/4h
ATE US (dust, mist)	132 mg/l/4h

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 oral	8300 mg/kg body weight Animal: mouse
LD50 dermal rabbit	> 15800 mg/kg body weight (Rabbit, Experimental value, Dermal)
LC50 Inhalation - Rat	124.7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	8300 mg/kg body weight

Methanol (67-56-1)	
LD50 oral rat	1187 – 2769 mg/kg body weight (BASF test, Rat, Male / female, Experimental value, 15-35 % aqueous solution, Oral, 7 day(s))
LD50 dermal rabbit	17100 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)
LC50 Inhalation - Rat	128.2 mg/l air (BASF test, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1187 mg/kg body weight
ATE US (dermal)	17100 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

Skin corrosion/irritation : Not classified

acetone (67-64-1)	
pH	5 – 6 (20 °C)

ethanol (64-17-5)	
pH	7 (789 g/l, 20 °C)

Methanol (67-56-1)	
pH	No data available in the literature

Serious eye damage/irritation : Causes serious eye irritation.

acetone (67-64-1)	
pH	5 – 6 (20 °C)

ethanol (64-17-5)	
pH	7 (789 g/l, 20 °C)

Methanol (67-56-1)	
pH	No data available in the literature

Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : May cause cancer.

ethanol (64-17-5)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity : Not classified  
STOT-single exposure : Causes damage to organs. May cause drowsiness or dizziness.



# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.
STOT-repeated exposure	: Not classified
ethanol (64-17-5)	
NOAEL (subchronic,oral,animal/male,90 days)	< 9700 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic,oral,animal/female,90 days)	> 9400 mg/kg body weight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified  
Viscosity, kinematic : No data available

acetone (67-64-1)	
Viscosity, kinematic	No data available in the literature
ethanol (64-17-5)	
Viscosity, kinematic	1.6 mm <sup>2</sup> /s (20 °C)

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.  
Symptoms/effects after skin contact : None under normal conditions.  
Symptoms/effects after eye contact : Eye irritation.  
Symptoms/effects after ingestion : None under normal conditions.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
ethanol (64-17-5)	
LC50 - Fish [1]	15300 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 72h - Algae [1]	275 mg/l (Equivalent or similar to OECD 201, Chlorella vulgaris, Static system, Fresh water, Experimental value, Growth rate)
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'
Methanol (67-56-1)	
LC50 - Fish [1]	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)
EC50 96h - Algae [1]	22000 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Methanol (67-56-1)</b>	
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	446.7 mg/l Test organisms (species): Pimephales promelas Duration: '28 d'

### 12.2. Persistence and degradability

<b>Gram Stain, Decolorizer 75 25</b>	
Persistence and degradability	Not rapidly degradable

<b>acetone (67-64-1)</b>	
Persistence and degradability	Biodegradable in the soil, Biodegradable in the soil under anaerobic conditions, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance

<b>ethanol (64-17-5)</b>	
Persistence and degradability	Biodegradable in the soil, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.8 – 0.967 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.7 g O <sub>2</sub> /g substance
ThOD	2.1 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.43

<b>Methanol (67-56-1)</b>	
Persistence and degradability	Readily biodegradable in the soil, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance
ThOD	1.5 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

<b>acetone (67-64-1)</b>	
BCF - Fish [1]	0.69 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

<b>ethanol (64-17-5)</b>	
Partition coefficient n-octanol/water (Log Pow)	-0.35 (Experimental value, Equivalent or similar to OECD 107, 24 °C)
Bioaccumulative potential	Not bioaccumulative.

<b>Methanol (67-56-1)</b>	
BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.4. Mobility in soil

#### acetone (67-64-1)

Surface tension	23.3 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

#### ethanol (64-17-5)

Surface tension	22.31 mN/m (20 °C, 100 %)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.2 (log Koc, Experimental value)
Ecology - soil	Highly mobile in soil.

#### Methanol (67-56-1)

Mobility in soil	2.75 Source: HSDB
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	-0.89 – -0.21 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapors may accumulate in the container. Do not re-use empty containers.

## SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

### 14.1. UN number

UN-No.(DOT)	: UN1170
UN-No. (TDG)	: UN1170
UN-No. (IMDG)	: 1170
UN-No. (IATA)	: 1170

### 14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Ethanol solutions
Proper Shipping Name (TDG)	: ETHANOL SOLUTION
Proper Shipping Name (IMDG)	: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
Proper Shipping Name (IATA)	: Ethanol solution

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 3  
Hazard labels (DOT) : 3



#### TDG

Transport hazard class(es) (TDG) : 3  
Hazard labels (TDG) : 3



#### IMDG

Transport hazard class(es) (IMDG) : 3  
Hazard labels (IMDG) : 3



#### IATA

Transport hazard class(es) (IATA) : 3  
Hazard labels (IATA) : 3



### 14.4. Packing group

Packing group (DOT) : II  
Packing group (TDG) : II  
Packing group (IMDG) : II  
Packing group (IATA) : II

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### DOT

UN-No.(DOT) : UN1170

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	:	24 - Alcoholic beverages containing more than 70 percent alcohol by volume must be transported as materials in Packing Group II. Alcoholic beverages containing more than 24 percent but not more than 70 percent alcohol by volume must be transported as materials in Packing Group III. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	4b;150
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	202
DOT Packaging Bulk (49 CFR 173.xxx)	:	242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	60 L
DOT Vessel Stowage Location	:	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

### TDG

UN-No. (TDG)	:	UN1170
TDG Special Provisions	:	150 - An approved ERAP is required for the dangerous goods referred to in paragraph 7.2(1)(f) of Part 7 (Emergency Response Assistance Plan).
Explosive Limit and Limited Quantity Index	:	1 L
Excepted quantities (TDG)	:	E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	:	5 L
Emergency Response Guide (ERG) Number	:	127

### IMDG

Special provision (IMDG)	:	144
Limited quantities (IMDG)	:	1 L
Excepted quantities (IMDG)	:	E2
Packing instructions (IMDG)	:	P001
IBC packing instructions (IMDG)	:	IBC02
Tank instructions (IMDG)	:	T4
Tank special provisions (IMDG)	:	TP1
EmS-No. (Fire)	:	F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	:	S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	:	A
Properties and observations (IMDG)	:	Colourless, volatile liquids. Pure ETHANOL: flashpoint 13°C c.c. Explosive limits: 3.3% to 19%. Miscible with water.

### IATA

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y341
PCA limited quantity max net quantity (IATA)	:	1L
PCA packing instructions (IATA)	:	353
PCA max net quantity (IATA)	:	5L
CAO packing instructions (IATA)	:	364
CAO max net quantity (IATA)	:	60L
Special provision (IATA)	:	A3, A58, A180
ERG code (IATA)	:	3L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

acetone	CAS-No. 67-64-1	25%
---------	-----------------	-----

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Methanol	CAS-No. 67-56-1	3.75%
----------	-----------------	-------

#### Methanol (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	5000 lb
-----------	---------

#### 15.2. International regulations

##### CANADA

#### ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

##### EU-Regulations

No additional information available

##### National regulations


#### ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Methanol (67-56-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### 15.3. US State regulations

 **WARNING:** This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	State or local regulations
ethanol(64-17-5)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Methanol(67-56-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List

# Gram Stain, Decolorizer 75 25

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H350	May cause cancer
H370	Causes damage to organs

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness